

DEAR SIR,

KINDLY PROVIDE THE FOLLOWING DETAILS TO SERVE YOU BETTER

VALVE TYPE	2 WAY / 3 WAY
PIPE SIZE	1/8 " TO 4 "
END CONNECTION	BSP(F) / NPT(F) / FLANGE END - ASA150#R.F
BODY MATERIAL	BRASS / S.S.304 / S.S.316 / CAST BRONZE / ZINC / ALUMINUM / CAST IRON
MEDIUM	AIR / WATER / OIL/ STEAM / INERT GAS / L.D.OIL / LPG/ PROPENE GAS/ CNG/OTHERS
SUPPLY	AC / DC
OPERATING PRESSURE	IN KG / CM2 / BAR / PSI
OPERATION	NORMALLY CLOSED / NORMALLY OPEN / UNIVERSAL
COIL TYPE	18" LEAD / SCREWED TERMINAL / 3 PIN
COIL INSULATION	CLASS " F " / CLASS " H"
SEAL	NEOPRENE / VITON / TEFLON
EXTRA FEATURES	MANUAL OVERRIDE / MANUAL RESET / SILENCER
COIL ENCLOSURE	IP20/ IP40/ IP55/ IP56/ IP65/ IP66/ IP67/ FLAMEPROOF (IIA /IIB)
FLUID TEMPERATURE	IN DEGREES °C / °F
ORIFICE	FULL PORT / AS REQUIRED
QUANTITY REQUIRED	IN NUMBERS

PRECISION INSTRUMENT CO.

124, A to Z Industrial Estate, G. K. Marg , Lower Parel Mumai 400013.

[Tel:- 022-24926384](tel:022-24926384),[022-40040030](tel:022-40040030). Mobile:-9920760124

Email Id:- sales@floconvalves.com

www.floconvalves.com